

## GENELEC 8020B



Cod.Art. : 8612

Produttore : Genelec

### MONITOR DA STUDIO BIAMPLIFICATO

The small Genelec 8020B (Height with Iso-Pod™ 242 mm, Width 151 mm and Depth 142 mm) has been designed for monitoring in difficult listening environments, particularly those compromised by lack of space. However, size is no handicap to performance as the 8020A two-way active monitoring system incorporates Genelec's acoustic design innovations to minimise all forms of distortion.

The 8020B has a die-cast aluminium Minimum Diffraction Enclosure (MDE™), which features relatively large internal volumes; softly curved edges and outstanding mechanical strength. As a result, the imaging accuracy and low frequency extension with such a compact enclosure are truly astounding.

The 8020B also incorporates the advanced Directivity Control Waveguide (DCW™), which provides an amazingly smooth on and off axis response; while the long, curved reflex port ends in a wide flare for excellent bass articulation

### Caratteristiche

Input format: Analog

SPL :

Maximum short time sine wave acoustic output at 1 m on axis in half space, averaged from 100 Hz to 3 kHz ; 95 dB

SPL

Maximum peak acoustic output per pair with music material ; 105 dB SPL @ 1m

Drivers :

## GENELEC 8020B

Bass 105 mm (4")  
Treble 19 mm (3/4") metal dome  
Crossover frequencies 3 kHz  
Free field frequency response 66 Hz - 20 kHz ( $\pm 2.5$  dB)  
Amplifier power /ch :  
Bass 20 W  
Treble 20 W  
Dimensioni: (H x W x D) :  
mm 226 x 151 x 142 mm (Height with Iso-Pod™ 242 mm)  
inches 8 7/8 x 6 x 5 5/8" (Height with Iso-Pod™ 9 1/2")  
Peso: 3.7 kg (8.1 lb)  
Colore: antracite

Prezzo : €319,00 IVA inclusa (€263,64 esclusa IVA)

---